



ULTRA HIGH PERFORMANCE

SUV



CHAMPIRO 528



- 20 – 22 Inch
- Speed Rating: V
- 45 – 55 Series
- UTQG: 320AA

Features

Unique and dynamic tread design with progressive elements

Streamlined high-angle grooves

Wide casing profile and variable pitch design

Benefits

- ▶ Outstanding handling stability
- ▶ Efficient water dispersion at high speeds and wet traction
- ▶ Comfortable and quiet performance



* See warranty brochure for details





CHAMPIRO 528


Size Range


AR	Tire Size	LI	SR	Approved Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		UTQG
						lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm	
35	265/35R22	102	V	9 1/2J	9J;10J	1874	850	49	340	11	8.3	25.4	644	10.7	271	300AA
40	305/40R22	114	V	11J	10 1/2J;11 1/2J	2601	1180	49	340	11	8.7	31.6	803	12.3	313	300AA
	275/45R20	110	V	9J	8 1/2J;9 1/2J	2337	1060	49	340	11	8.4	29.8	756	10.7	273	300AA
45	285/45R22	114	V	9 1/2J	9J;10J;11J	2601	1180	49	340	11	8.5	32.1	815	11.2	285	300AA
	305/45R22	118	V	10J	9 1/2J;11J	2910	1320	49	340	11	8.7	32.8	833	12.0	305	300AA
50	285/50R20	116	V	9J	8 1/2J;9 1/2J;10J	2756	1250	49	340	11	8.5	31.3	794	11.7	297	300AA
	295/50R20	118	V	9 1/2J	9J;10J;10 1/2J	2910	1320	49	340	11	8.6	31.7	804	12.2	309	300AA
55	275/55R20	117	V	8 1/2J	8J;9J	2833	1285	49	340	11	8.6	31.9	810	11.2	284	300AA

LI Load Index SR Speed Rating

A  Wide road contact tread provides excellent grip, maneuverability and braking

C  Circumferential central rib for high speed stability and control

B  Streamline pattern and dual circumferential grooves for ultra-efficient water evacuation and wet traction

D  Robust shoulder pattern design provides tread stability, efficient response and control at high speed cornering

