


PREMIUM STUDDABLE WINTER

CHAMPIRO ICEPRO



Comfort



Studdable



Directional



Winter



Studdable

14-18 Inch

SR: Q & T

55-75 Series



Features

New innovative studdable design

Specially designed stud distribution

Lateral groove pattern design

New Silica compound

Benefits

▶ Reliable in extreme weather conditions

▶ Enhances grip and reduces noise levels

▶ Effectively removes slush and ice from the contact area

▶ Enhances ice performance and snow traction

* See warranty brochure for details

PREMIUM STUDDABLE WINTER

CHAMPIRO ICEPRO



PCR Size Range

AR	Tire Size	LI	SR	Approved Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width	
						lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm
55	205/55R16 XL	94	T	6 1/2J	6J;7J	1356	615	44	300	12	9.7	24.9	632	8.1	205
	185/60R15	84	T	5 1/2J	5J;6J	1102	500	44	300	12	9.7	23.7	603	7.3	185
	195/60R15	88	T	6J	5 1/2J;6 1/2J;7J	1235	560	44	300	12	9.7	24.2	615	7.7	195
	205/60R16 XL	96	T	6J	5 1/2J ;6 1/2J	1389	630	44	300	12	9.7	25.7	652	8.1	205
	215/60R16	95	T	6 1/2J	5 1/2J;6J;7J	1521	690	44	300	12	9.7	26.1	664	8.5	215
	215/60R17	96	T	6 1/2J	5 1/2J;6J;7J	1565	710	44	300	13	10.2	27.2	690	8.5	215
	225/60R16	98	T	6 1/2J	6J;7J;7 1/2J	1653	750	44	300	12	9.7	26.2	676	8.9	225
60	225/60R17	99	T	6 1/2J	6J;7J;7 1/2J	1708	775	44	300	13	10.2	27.6	702	8.9	225
	175/65R14 XL	86	T	5J	5B;5 1/2J;6J	1047	475	44	300	12	9.7	22.9	584	6.9	175
	185/65R14 XL	90	T	5 1/2J	5J;6J;6 1/2J	1168	530	44	300	12	9.7	23.5	596	7.3	185
	185/65R15 XL	92	T	5 1/2J	5J;6J	1235	560	44	300	12	9.7	24.4	621	7.3	185
	195/65R15 XL	95	T	6J	5 1/2J;6 1/2J;7J	1356	615	44	300	12	9.7	25.0	635	7.7	195
	205/65R15	94	T	6J	5 1/2J;6 1/2J;7J	1477	670	44	300	12	9.7	25.5	647	8.1	205
	215/65R16 XL	102	T	6 1/2J	6J;7J	1653	750	44	300	12	9.7	27.0	686	8.5	215
70	205/70R15	96	T	6J	5 1/2J;6 1/2J;7J	1565	710	44	300	12	9.7	26.3	669	8.1	205

SUV Size Range

60	245/60R18	105	T	7J	7 1/2J;8J; 8 1/2J	2039	925	44	300	13	10.2	29.6	751	9.8	248
65	275/65R18	116	T	8J	7 1/2J;8 1/2J;9J	2756	1250	44	300	13	10.2	32.1	815	11.0	279
	215/70R15	98	T	6 1/2J	6J;7J	1653	750	44	300	13	10.2	26.8	681	8.7	220
70	215/70R16	100	T	6 1/2J	6J;7J	1764	800	44	300	13	10.2	27.9	708	8.7	220
	225/70R16	103	T	6 1/2J	6J;7J	1929	875	44	300	13	10.2	28.4	722	8.9	227
	235/70R16	106	T	7J	6 1/2J;7 1/2J	2094	950	44	300	13	10.2	28.9	736	9.4	240
	245/70R17	110	T	7J	6 1/2J;7 1/2J	2337	1060	44	300	13	10.2	30.5	776	9.8	248
	265/70R17	115	T	8J	7 1/2J;8 1/2J	2679	1215	44	300	13	10.2	31.7	804	10.7	272

Light Truck Size Range

65	LT275/65R18	123/ 120	Q	8J	7 1/2J,8J, 8 1/2J,9J	3415/ 3085	1550/ 1400	80	550	17	13.5	32.1	815	11.0	279
	LT245/70R17	119/ 116	Q	7J	6 1/2J,7J, 7 1/2J,8J	3000/ 2755	1360/ 1250	80	550	17	13.5	30.8	782	9.8	248
70	LT265/70R17	121/ 118	Q	8J	7J,7 1/2J,8J, 8 1/2J	3195/ 2910	1450/ 1320	80	550	17	13.5	31.9	810	10.7	272
	LT225/75R16	115/ 112	Q	6J	6K,6J,6 1/2K, 6 1/2J,7K,7J	2680/ 2470	1215/ 1120	80	550	17	13.5	29.5	750	8.8	223
75	LT245/75R16	120/ 116	Q	7J	6 1/2K,6 1/2J,7J, 7K,7 1/2J,8J	3042/ 2778	1380/ 1260	80	550	17	13.5	30.8	784	9.5	242

LI Load Index SR Speed Rating