


PREMIUM TOURING

8 0 0 0 0 MILES
Limited Warranty *



MAXTOUR



13 – 16 Inch Speed Rating: T
60 – 75 Series UTQG: 620AB

Features

- Advanced tread pattern
- Modern casing structure
- Enhanced tread compound

Benefits

- ▶ Smooth, quiet and reliable performance
- ▶ Consistent endurance and durability
- ▶ Extended tread life



* See warranty brochure for details

PREMIUM TOURING

MAXTOUR



Size Range

AR	Tire Size	LI	SR	Approved Rim	Rim Width Range	Max. Load		Max. Pressure		Tread Depth		Overall Diameter		Section Width		Side wall	UTQG
						lbs	kg	psi	kpa	32 nd	mm	inch	mm	inch	mm		
60	185/60R14	82	T	5 1/2J	5J;6J	1047	475	36	250	12	9.0	22.8	578	7.4	189	BSW	620AB
	195/60R14	86	T	6J	5 1/2J;6 1/2J	1168	530	36	250	12	9.1	23.2	590	7.9	201	BSW	620AB
	195/60R15	88	T	6J	5 1/2J;6 1/2J	1235	560	36	250	12	9.1	24.2	615	7.9	201	BSW	620AB
	205/60R15	91	T	6J	5 1/2J;6 1/2J	1356	615	36	250	12	9.2	24.7	627	8.2	209	BSW	620AB
	215/60R16	95	T	6 1/2J	6J;7J	1521	690	36	250	12	9.3	26.1	664	8.7	221	BSW	620AB
	225/60R16	98	T	6 1/2J	6J;7J	1653	750	36	250	12	9.4	26.6	676	9.0	228	BSW	620AB
	235/60R16	100	T	7J	6 1/2J;7 1/2J	1764	800	36	250	12	9.5	27.1	688	9.4	240	BSW	620AB
	215/60R17	96	T	6 1/2J	6 1/2J	1565	1565	36	250	12	9.3	27.5	690	9.5	241	BSW	620AB
	P225/60R17	98	T	6 1/2J	6J;7J;7 1/2J	1653	750	44	300	12	9.3	31.9	702	8.9	225	BSW	620AB
65	175/65R14	82	T	5J	5 1/2J;6J	1047	475	36	250	11	8.9	23.0	584	7.0	177	BSW	620AB
	185/65R14	86	T	5 1/2J	5J;6J	1168	530	36	250	12	9.0	23.5	596	7.4	189	BSW	620AB
	195/65R14	89	T	6J	5 1/2J;6 1/2J	1279	580	36	250	12	9.1	24.0	610	7.9	201	BSW	620AB
	185/65R15	88	T	5 1/2J	5J;6J	1235	560	36	250	12	9.0	24.4	621	7.4	189	BSW	620AB
	195/65R15	91	T	6J	5 1/2J;6 1/2J	1356	615	36	250	12	9.1	25.0	635	7.9	201	BSW	620AB
	205/65R15	94	T	6J	5 1/2J;6 1/2J	1477	670	36	250	12	9.2	25.5	647	8.1	205	BSW	620AB
	215/65R15	96	T	6 1/2J	6J;7J	1565	710	36	250	12	9.3	26.0	661	8.7	221	BSW	620AB
	215/65R16	98	T	6 1/2J	6J;7J	1653	750	36	250	12	9.3	27.0	686	8.7	221	BSW	620AB
	235/65R17	104	T	7J	6 1/2J;7 1/2J	1984	900	36	250	12	9.5	29.1	738	9.4	240	BSW	620AB
70	175/70R13	82	T	5.00B	5J;5.50B	1047	475	36	250	12	9.1	22.7	576	7.0	177	BSW	620AB
	185/70R13	86	T	5.50B	5 1/2J;6.00B	1168	530	36	250	12	9.2	23.2	590	7.4	189	BSW	620AB
	185/70R14	88	T	5 1/2J	5J;6J	1235	560	36	250	12	9.2	24.3	616	7.4	189	BSW	620AB
	195/70R14	91	T	6J	5 1/2J;6 1/2J	1356	615	36	250	11	8.7	24.8	630	7.9	201	BSW	620AB
	205/70R14	95	T	6J	5 1/2J;6 1/2J	1521	690	36	250	11	8.8	25.4	644	8.2	209	BSW	620AB
	205/70R15	96	T	6J	5 1/2J;6 1/2J	1565	710	36	250	11	8.8	26.3	669	8.2	209	BSW	620AB
	205/70R15 WR	96	T	6J	5 1/2J;6 1/2J	1565	710	36	250	11	8.8	26.3	669	8.2	209	WW	620AB
	215/70R15	98	T	6 1/2J	6J;7J	1653	750	36	250	11	8.9	26.9	683	8.7	221	BSW	620AB
	215/70R15 WR	98	T	6 1/2J	6J;7J	1653	750	36	250	11	8.9	26.9	683	8.7	221	WW	620AB
	225/70R15	100	T	6 1/2J	6J;7J	1764	800	36	250	12	9.0	27.4	697	9.0	228	BSW	620AB
	235/70R15	103	T	7J	6 1/2J;7 1/2J	1929	875	36	250	12	9.1	28.0	711	9.4	240	BSW	620AB
	235/70R15 WR	103	T	7J	6 1/2J;7 1/2J	1929	875	36	250	12	9.1	28.0	711	9.4	240	WW	620AB
	225/70R16	102	T	6 1/2J	6J;7J	1874	850	36	250	12	9.0	28.4	722	9.0	228	BSW	620AB
	235/70R16	106	T	7J	6 1/2J;7 1/2J	2094	950	36	250	12	9.1	29.0	736	9.4	240	BSW	620AB
75	185/75R14	89	T	5J	4 1/2J;5 1/2J	1279	580	36	250	12	9.2	25.0	634	7.2	184	BSW	620AB
	195/75R14	92	T	5 1/2J	5J;6J	1389	630	36	250	12	9.3	25.5	648	7.7	196	BSW	620AB
	205/75R14	95	T	5 1/2J	5J;6J	1521	690	36	250	12	9.4	26.1	664	8.0	203	BSW	620AB
	205/75R15	97	T	5 1/2J	5J;6J	1609	730	36	250	12	9.4	27.1	689	8.0	203	BSW	620AB
	215/75R15	100	T	6J	5 1/2J;6 1/2J;7J	1764	800	36	250	12	9.5	27.7	703	8.5	216	BSW	620AB
	225/75R15	102	T	6J	6 1/2J;7J	1874	850	36	250	12	9.6	28.3	719	8.8	223	BSW	620AB
	235/75R15	105	T	6 1/2J	6J;7J	2039	925	36	250	12	9.7	28.9	733	9.3	235	BSW	620AB

LI Load Index SR Speed Rating