


ALL TERRAIN LIGHT TRUCK AND SUV



LIMITED
5 YEAR
WARRANTY

ADVENTURO A/T II



- 15 – 18 Inch
- 65 – 85 Series
- Speed Rating: S-T
- UTQG: 400AB

Features

Unique tread design with continuous central block

Open shoulder grooves and wide lugs

Full nylon cap ply

Balanced void ratio

Benefits

▶ Excellent handling stability

▶ Superior all-surface traction for all weather conditions

▶ Improves stability and handling

▶ Resistance to aquaplaning and consistent wet traction



* See warranty brochure for details

ALL TERRAIN LIGHT TRUCK & SUV

ADVENTURO A/T II



Size Range

| AR | Tire Size | LI | SR | UTQG/ LR | Approved Rim | Rim Width Range | Max. Load | | Max. Pressure | | Tread Depth | | Overall Diameter | | Section Width | | Side Wall |
|----|-------------|----------|----|----------|--------------|------------------------------|------------|------------|---------------|-----|------------------|------|------------------|-----|---------------|-----|-----------|
| | | | | | | | lbs | kg | psi | kpa | 32 nd | mm | inch | mm | inch | mm | |
| 65 | P275/65R18 | 114 | T | 400AB | 8J | 7 1/2J;8 1/2J; 9J;9 1/2J | 2601 | 1180 | 44 | 300 | 13 | 10.2 | 32.1 | 815 | 11.0 | 279 | OWL |
| | P255/70R17 | 110 | S | 400AB | 7 1/2J | 6 1/2J;7J; 8J;8 1/2J | 2337 | 1060 | 44 | 300 | 13 | 10.2 | 31.1 | 790 | 10.2 | 260 | OWL |
| 70 | LT305/70R16 | 124/ 121 | S | E | 9J | 8 1/2J;9 1/2J | 3525/ 3195 | 1600/ 1450 | 65 | 450 | 17 | 13.5 | 33.1 | 840 | 12.0 | 305 | OWL |
| | LT235/75R15 | 104/ 101 | S | C | 6 1/2J | 6JK;6J;7J | 1985/ 1820 | 900/ 825 | 51 | 350 | 15 | 12.1 | 29.1 | 739 | 9.3 | 235 | OWL |
| 75 | LT215/75R16 | 110/ 108 | S | D | 6J | 5 1/2J;6 1/2J | 2335/ 2205 | 1060/ 1000 | 65 | 450 | 15 | 11.9 | 28.7 | 728 | 8.5 | 215 | OWL |
| | LT225/75R16 | 115/ 112 | S | E | 6J | 6K;6 1/2K; 6 1/2L;6 1/2J | 2680/ 2470 | 1215/ 1120 | 80 | 550 | 17 | 13.1 | 29.3 | 744 | 8.9 | 225 | OWL |
| | LT245/75R16 | 120/ 116 | S | E | 7J | 6 1/2K;6 1/2L; 6 1/2J;7 1/2J | 3042/ 2778 | 1380/ 1260 | 80 | 550 | 17 | 13.1 | 30.7 | 780 | 9.6 | 245 | OWL |
| | LT265/75R16 | 112/ 109 | S | C | 7 1/2J | 7K;7L;7J; 8L;8J | 2470/ 2271 | 1120/ 1030 | 51 | 350 | 17 | 13.1 | 31.7 | 804 | 10.4 | 265 | OWL |
| | LT285/75R16 | 122/ 119 | S | D | 8J | 7 1/2J;8L;8LB; 8KB;8 1/2J | 3305/ 3000 | 1500/ 1360 | 65 | 450 | 17 | 13.3 | 32.8 | 834 | 11.2 | 285 | OWL |
| 85 | LT235/85R16 | 120/ 116 | S | E | 6 1/2J | 6J;6K;6L; 6 1/2L;7J;7K;7L | 3042/ 2778 | 1380/ 1260 | 80 | 550 | 17 | 13.1 | 31.7 | 806 | 9.3 | 235 | OWL |

LI Load Index SR Speed Rating OWL Outline White Letter

